FOXJET®

AN ITW COMPANY

LinxSeries®7900

## Continuous InkJet Printing

Inkjet
Technology by

LINX

Dimensions:

Front Elevation

240 mm

490 mm

Top Elevation

600 mm

490 mm

Side Elevation

240 mm

663 mm (including clearance at back of printer)

Printer Specifications:

Printhead with 2M Conduit, Standard	MK7
Printhead/Conduit Options	4M, 90D, Short Reach 90D
Max Lines of Print	3 Standard, 5 Optional
Character Height Range	0.04" to 0.54"
Max Speed; Single Line Print	1230 fpm
Ink Range	Dye Based, Pigmented with Spectrum
Automatic Date Codes, Sequential Numbering	Yes
Timed Messages	Yes
Graphics/Logo Printing	Yes
Barcodes, Common Linear & 2D Datamatrix	Yes
Memory Capacity (# of Messages)	999
Ingress Protection Rating	IP55, Optional IP65, Spectrum IP65 as standard
Base and Enclosure	Stainless Steel
Operating Temperature Range	41-113°F
Humidity Range (r.h., Non-Condensing)	90% Max
Power Supply	100-230V 50/60 Hz
Power Consumption	200W
Weight	46.3-52.9 lbs
Regulatory Approvals	TÜV/GS, CE Mark, FCC, RoHS

Connections / Interfacing Specifications:

Logojet PC Based Message and Logo Creation Software and DDE Driver Software	Optional
RS232 Port	Yes
Ethernet Option	Yes
Parallel I/O Option	Yes
USB Port for Message and Printer Setting Back Up and Restore	Yes
Shaft Encoder, Product Detector, External Single Stage Alarm, Volt-Free Contact Alarm Connection	Yes

Features and Benefits:

- **Single Button** startup and shutdown.
- **Data Matrix and 3-line printing** is standard, with optional 4 or 5 line printing.
- **Quickswitch TM software** allows for fast, easy code changes using a bar code scanner.
- **LINXInsight ® Remote Web control** enables remote monitoring from a smartphone, plus message download and control from a PC.
- **Future Proof** additional lines of print, faster print speeds and remote communication tools can be added as you need them.
- **Integral USB port** allows for trouble free copy and backup of data, transfers of message content and setup of data between printers.
- **Full-flushTM system** automatically cleans and dries the printhead and conduit at every shutdown, minimizing manual cleaning.
- **SureFill® fluid replenishment** ensures fast, mistake proof refills while printing ensure maximum uptime.
- **18 Month Warranty** on printer at no extra cost (excludes Spectrum & Food Grade models).
- **Dynamically adjusted service intervals** up to 9,000 hours.
- **Wide range of message formats** available including logos and barcodes. Create custom graphics with Logo Editor.

Distributor Information:

videos

inkjet coders

product info

scan me