

NEW · NEW · NEW · NEW

**NEW 15mm (5/8") glue gun**

**Improved quality, low cost**

The new tec 806-15 strikes a similar balance of quality, reliability and affordability as the class-leading 805-15, while boasting some useful additional features.

- Soft-grip handle for improved comfort
- A more efficient eco melt chamber design for faster and easier adhesive application
- Power cord lengthened from 2m to 3m
- Protective mouldings around the on/off switch to prevent accidental operation

**Efficient & easy to use**

With an improved heater housing, the tec 806-15 is easier to use for longer. The 806-15 also offers increased output compared to similar 12mm guns, delivering up to 30% more molten glue per trigger pull. It can hold up to 60% more glue too, meaning it doesn't need to be reloaded as often.

- Designed to ensure optimum safety and user-comfort with a new soft-feel grip
- Features an adjustable trigger, allowing alterations to be made to suit different hand sizes, or to achieve different outputs per trigger pull
- Includes a sturdy base, so the gun can be stood up between uses with no risk of the glue melting back
- Easy-to-clean nozzle shroud means that any dried glue can be wiped off to keep your gun in good condition

**Fast warm-up**

The tec 806-15 is ready for use almost immediately, with a fast heat up time of only 2-3 minutes from cold. The tec 806-15 can operate on any voltage from 110V to 240V due to its PTC self-regulating heater, offering users even more flexibility. The tec 806-15 meets worldwide electrical standards and is covered by a 12 month warranty.



The soft-grip handle and new heater housing make the tec 806 comfortable to use and easier to operate

**tec 806-15**

Low cost medium size industrial 15mm (5/8") glue gun, eco heater chamber design for low power consumption, robust & easy to use. Medium output, 3 minute warm-up time & illuminated on/off switch.

<b>Melt rate</b>	1.8kg (4lbs)/hr
<b>Glue size</b>	15mm (5/8") glue stick
<b>Voltage</b>	110V - 240V
<b>Wattage</b>	25W (250W)
<b>Heater</b>	PTC
<b>Temp Control</b>	Self regulating heater
<b>Hotmelt gun °C (°F)</b>	195°C (380°F)
<b>Lowmelt gun °C (°F)</b>	130°C (265°F)
<b>Power cable</b>	3m (10 ft)
<b>Weight</b>	450g (16oz)
<b>Packaging</b>	PET blister (10 per ctn)

**Ideal for...** a range of industrial applications, from crafting and floristry through to woodworking and product assembly



**1**  
**Woodworking**  
The tec 806-15 can be used for a range of woodworking applications, with a good output and smooth operation.



**2**  
**Product assembly**  
It is ideal for product assembly too, and the slim profile of the 806 means that the adhesive can be accurately applied.



**3**  
**Packaging**  
Robust and reliable, the tec 806 is also ideal for a range of carton closing and packaging applications.