



Meets ANSI/ESD S20.20 tested per ANSI/ESD S1.1 and ESD TR53.

The 2200 Series Coil Cord is for use with Single-Wire Wrist Straps and SCS Workstation Continuous Monitors (sold separately). The Coil Cord features a segmented strain relief and a single bundle of tinsel conductors which provide long cord life and flexible movement. It has a 1 megohm current limiting resistor (at the socket end to attach to the wristband). An alligator clip is included but best to plug banana plug into a banana jack ground.



Specifications	Typical Value
Tensile strength	> 15 lbs. (6.8 kg)
Flex life bending	1,000,000 cycles
Resistance end-to-end	1 Megohm $\pm$ 20%
Plug	3.4mm straight banana plug
Socket	4mm female snap socket
Color	Black

Item	Description
<a href="#">2210</a>	5 ft. Coil Cord
<a href="#">2220</a>	10 ft. Coil Cord

Unless otherwise noted, tolerance  $\pm$ 10%

Specifications and procedures subject to change without notice.

Made in the United States of America with Globally Sourced Materials.

### 2200 SERIES COIL CORD

926 JR Industrial Drive, Sanford, NC 27332  
WEB SITE: [StaticControl.com](http://StaticControl.com)  
PHONE (919) 718-0000

**DRAWING  
NUMBER**  
2200 Series

**DATE**  
July  
2017

# SCS